

Hydrogen storage device

M266 E40 000

**The hydrogen storage device
supplies the AP2C with hydrogen. It
can be refilled 25 times or used as a
consumable.**



Packaging

It is an aluminum cylinder with a shrouded connector that locks into the AP2C's handle.

The device is filled with hydrogen adsorbed on to lanthanum nickel powder.

The advantage of this method is that a large quantity of hydrogen can be stored without pressure, thus providing reliability in use and storage.

By using a refilling bench, the cartridge can be refilled 25 times with hydrogen (Ref.: M175 E00 000).

The hydrogen storage device can be stored for 10 years.

Characteristics

Size: L 168 mm Ø 26 mm (L 6.61" Ø 1.02")

Weight: 230 gr

Autonomy: 12 hours

Volume of hydrogen: 24 liters

Operating temperature: -32°C to +55°C (-25.6°F to +131°F)

Storage temperature: -39°C to +71°C (-38.2°F to +160°F)

PROENGIN	PROENGIN Inc
1, rue de l'Industrie 78210 Saint-Cyr L'Ecole FRANCE	405 N.E. 8 th street Fort Lauderdale Florida 33304 USA
Tel: (33) 1 30 58 47 34 / Fax: (33) 1 30 58 93 51	Tel: (1) 954 760 99 90 / Fax: (1) 954 760 99 55
E-Mail: contact@proengin.com	E-Mail: contactusa@proengin.com